

1. Unique identification code of the product-type:

2. Intended use or uses:

3. Manufacturer:

4. Authorized representative:

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

Assessment system:

6a. Harmonised standard:

Notified unit/s:

6b. European Assessment Document:

European Technical Assessment:

Technical Assessment Body:

Notified unit/s:

7. Declared performances:

Essential characteristics	Levels and/or classes	Reference document
Reaction to fire		
Release of dangerous substances - glazed tiles:	-	-
- Lead [mg/dm ²]		
- Cadmium [mg/dm ²]		
- Other		
Bond strength / adhesion [N/mm ²]:	-	-
- cementitious adhesives		
- dispersion adhesives		
- reaction resin adhesives		
- mortar		
Thermal shock resistance		
Breaking strength [N]		
Slipperiness according to CEN/TS 16165:2021, Annex B - α_{shod} [°]		
Tactility		
Durability for:	-	-
- internal uses		
- external uses: freeze-thaw resistance		

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

NA - not applicable

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

on 2025/03/08



Applies to the product:

Group:

1. Detailed information about the application:

Characteristics	Levels and/or classes	Reference document
Thickness	mm	
The permissible deviation of the average width for each tile from the work size width		
The permissible deviation of the average length for each tile from the work size length		
The permissible deviation of the average thickness of each tile from the work size thickness		
The maximum permissible deviation from straightness, related to the corresponding work size (width)		
The maximum permissible deviation from straightness, related to the corresponding work size (length)		
The maximum permissible deviation from rectangularity related to the corresponding work size (width)		
The maximum permissible deviation from rectangularity related to the corresponding work size (length)		
The maximum permissible deviation from flatness centre curvature, related to diagonal calculated from the work sizes		
The maximum permissible deviation from flatness edge curvature, related to the corresponding work size (width)		
The maximum permissible deviation from flatness edge curvature, related to the corresponding work size (length)		
The maximum permissible deviation from flatness warpage, related to diagonal calculated from the work sizes		
Water absorption E _b [%]		
Breaking strength [N]		
Flexural tensile strength [N/mm ²]		
Resistance to deep abrasion - unglazed tiles [mm ³]		
Resistance to surface abrasion - glazed tiles, PEI/number of rotations		
Crazing resistance - glazed tiles		
Impact resistance		
Resistance to staining		
Resistance to low concentrations of acids and alkalis		
Resistance to high concentrations of acids and alkalis		
Resistance to household chemicals and swimming pool salts		
Natural radioactivity [Bq/kg]		
Slip - BARE FOOT		DIN EN 16165:2023-02, Attachment A
Slip - BARE FOOT α _{barefoot} [°]		EN 16165:2021, Attachment A
Slip resistance - R		DIN EN 16165:2023-02, Attachment B
Slip resistance (PTV) - risk of dry/wet slippage - slider 55		BS 7976-2:2002+A1:2013 / UKSRG
Slip resistance (PTV) - risk of dry/wet slippage - slider 96		BS 7976-2:2002+A1:2013 / UKSRG
Displacement area class / displacement surface		DIN 51130
Emissions of volatile organic compounds (VOCs) - class		ISO 16000
Thermal conductivity coefficient [W/m*K]		PN-EN 12664
Safety class of glass products		PN-EN 12600
Class UPEC		CSTB-Cahier 3778_V6

In accordance with the indicated use and properties declared in the DOP, the Product Data Sheet and observing the principles included in the assembly instructions in accordance with

2. Documents

Signed for and on behalf of the manufacturer by:

on 2025/03/08

