

Applies to the product: UNIWERSALNA LISTWA METALOWA ORO MAT PROFIL 2x75 G1  
Group: NA - not applicable

**1. Detailed information about the application:**

Characteristics	Levels and/or classes	Reference document
Thickness	7.5 mm	NA - not applicable
The permissible deviation of the average width for each tile from the work size width	± 0.9 mm	NA - not applicable
The permissible deviation of the average length for each tile from the work size length	± 0.6 %; ± 2.0 mm	NA - not applicable
The permissible deviation of the average thickness of each tile from the work size thickness	± 0.5 mm	NA - not applicable
The maximum permissible deviation from straightness, related to the corresponding work size (width)	± 0.75 mm	NA - not applicable
The maximum permissible deviation from straightness, related to the corresponding work size (length)	± 0.5 %; ± 1.5 mm	NA - not applicable
The maximum permissible deviation from rectangularity related to the corresponding work size (width)	± 0.75 mm	NA - not applicable
The maximum permissible deviation from rectangularity related to the corresponding work size (length)	± 0.5 %; ± 2.0 mm	NA - not applicable
The maximum permissible deviation from flatness centre curvature, related to diagonal calculated from the work sizes	± 0.5 %; ± 2.0 mm	NA - not applicable
The maximum permissible deviation from flatness edge curvature, related to the corresponding work size (width)	± 0.75 mm	NA - not applicable
The maximum permissible deviation from flatness edge curvature, related to the corresponding work size (length)	± 0.5 %; ± 2.0 mm	NA - not applicable
The maximum permissible deviation from flatness warpage, related to diagonal calculated from the work sizes	± 0.5 %; ± 2.0 mm	NA - not applicable
Water absorption E <sub>b</sub> [%]	≤ 0.5	NA - not applicable
Breaking strength [N]	NA - not applicable	NA - not applicable
Flexural tensile strength [N/mm <sup>2</sup> ]	NPD - no performance determined	NA - not applicable
Resistance to deep abrasion - unglazed tiles [mm <sup>3</sup> ]	NA - not applicable	NA - not applicable
Resistance to surface abrasion - glazed tiles, PEI/number of rotations	NA - not applicable	NA - not applicable
Crazing resistance - glazed tiles	Pass	NA - not applicable
Impact resistance	NPD - no performance determined	NA - not applicable
Resistance to staining	minimum 3 class	NA - not applicable
Resistance to low concentrations of acids and alkalis	LA class	NA - not applicable
Resistance to high concentrations of acids and alkalis	NA - not applicable	NA - not applicable
Resistance to household chemicals and swimming pool salts	A class	NA - not applicable
Natural radioactivity [Bq/kg]	f1 ≤ 1, f2 ≤ 240	NA - not applicable
Slip - BARE FOOT	NPD - no performance determined	DIN EN 16165:2023-02, Attachment A
Slip - BARE FOOT α <sub>barefoot</sub> [°]	NPD - no performance determined	EN 16165:2021, Attachment A
Slip resistance - R	NA - not applicable	DIN EN 16165:2023-02, Attachment B
Slip resistance (PTV) - risk of dry/wet slippage - slider 55	NA - not applicable	BS 7976-2:2002+A1:2013 / UKSRG
Slip resistance (PTV) - risk of dry/wet slippage - slider 96	N/A - not applicable	BS 7976-2:2002+A1:2013 / UKSRG
Displacement area class / displacement surface		DIN 51130
Emissions of volatile organic compounds (VOCs) - class	A+	ISO 16000
Thermal conductivity coefficient [W/m*K]	NPD - no performance determined	PN-EN 12664
Safety class of glass products	NA - not applicable	PN-EN 12600
Class UPEC	NA - not applicable	CSTB-Cahier 3778_V6

**In accordance with the indicated use and properties declared in the DOP, the Product Data Sheet and observing the principles included in the assembly instructions in accordance with "Regulation (EU) 223/988 of the European Parliament and of the Council of 10 May 2023 on general product safety", the product is safe.**

**2. Documents**

NA - not applicable

Signed for and on behalf of the manufacturer by:

**Kazimierz Ruczyński - Production Manager**  
on 2025/03/08

