

1. Unique identification code of the product-type:

5900144071773

2. Intended use or uses:

The ceramic tiles for internal and /or external floorings and walls, including stairs, in buildings and industrial facilities.

3. Manufacturer:

Ceramika Paradyż Sp. z o.o., ul. Piotrkowska 61, 26-300 Opoczno, Polska

4. Authorized representative:

NA - not applicable

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

Assessment system: 4

6a. Harmonised standard:

EN14411:2012

Notified unit/s:

NA - not applicable

6b. European Assessment Document:

NA - not applicable

European Technical Assessment:

NA - not applicable

Technical Assessment Body:

NA - not applicable

Notified unit/s:

NA - not applicable

7. Declared performances:

| Essential characteristics | Levels and/or classes | Reference document |
|----------------------------------------------------------------------------|---------------------------------|--------------------|
| Reaction to fire | A1 _{FL} | EN14411:2012 |
| Release of dangerous substances - glazed tiles: | - | - |
| - Lead [mg/dm ²] | ≤ 0.8 | EN14411:2012 |
| - Cadmium [mg/dm ²] | ≤ 0.07 | EN14411:2012 |
| - Other | NPD - no performance determined | EN14411:2012 |
| Breaking strength [N] | minimum 1300 | EN14411:2012 |
| Slipperiness according to CEN/TS 16165:2021, Annex B - α_{shod} [°] | $10 \leq \alpha_{shod} < 19$ | EN14411:2012 |
| Tactility | NPD - no performance determined | EN14411:2012 |
| Durability for: | - | - |
| - internal uses | Pass | EN14411:2012 |
| - external uses: freeze-thaw resistance | Pass | EN14411:2012 |

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

NA - not applicable

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Kazimierz Ruczyński - Production Manager

Opoczno on 2024/09/18



Applies to the product: INTERO MOCCA STOPNICA PROSTA NACINANA MAT. 29,8X119,8 G1
Group: BI_a

1. Detailed information about the application:

The ceramic tiles for internal and /or external floorings and walls, including stairs, in buildings and industrial facilities.

| Characteristics | Levels and/or classes | Reference document |
|----------------------------------------------------------------------------------------------------------------------|---------------------------------|------------------------------------|
| Thickness | 10.0 mm | EN14411:2012 |
| The permissible deviation of the average width for each tile from the work size width | ± 0.6 %; ± 2.0 mm | EN14411:2012 |
| The permissible deviation of the average length for each tile from the work size length | ± 0.6 %; ± 2.0 mm | EN14411:2012 |
| The permissible deviation of the average thickness of each tile from the work size thickness | ± 0.5 mm | EN14411:2012 |
| The maximum permissible deviation from straightness, related to the corresponding work size (width) | ± 0.5 %; ± 1.5 mm | EN14411:2012 |
| The maximum permissible deviation from straightness, related to the corresponding work size (length) | ± 0.5 %; ± 1.5 mm | EN14411:2012 |
| The maximum permissible deviation from rectangularity related to the corresponding work size (width) | ± 0.5 %; ± 2.0 mm | EN14411:2012 |
| The maximum permissible deviation from rectangularity related to the corresponding work size (length) | ± 0.5 %; ± 2.0 mm | EN14411:2012 |
| The maximum permissible deviation from flatness centre curvature, related to diagonal calculated from the work sizes | ± 0.5 %; ± 2.0 mm | EN14411:2012 |
| The maximum permissible deviation from flatness edge curvature, related to the corresponding work size (width) | ± 0.5 %; ± 2.0 mm | EN14411:2012 |
| The maximum permissible deviation from flatness edge curvature, related to the corresponding work size (length) | ± 0.5 %; ± 2.0 mm | EN14411:2012 |
| The maximum permissible deviation from flatness warpage, related to diagonal calculated from the work sizes | ± 0.5 %; ± 2.0 mm | EN14411:2012 |
| Water absorption E _b [%] | ≤ 0.5 | EN14411:2012 |
| Breaking strength [N] | minimum 1300 | EN14411:2012 |
| Flexural tensile strength [N/mm ²] | minimum 35 | EN14411:2012 |
| Resistance to deep abrasion - unglazed tiles [mm ³] | maximum 175 | EN14411:2012 |
| Resistance to surface abrasion - glazed tiles, PEI/number of rotations | NA - not applicable | EN14411:2012 |
| Crazing resistance - glazed tiles | Pass | EN14411:2012 |
| Impact resistance | NPD - no performance determined | EN14411:2012 |
| Resistance to staining | minimum 3 class | EN14411:2012 |
| Resistance to low concentrations of acids and alkalis | LB class | EN14411:2012 |
| Resistance to high concentrations of acids and alkalis | HB class | EN14411:2012 |
| Resistance to household chemicals and swimming pool salts | B class | EN14411:2012 |
| Natural radioactivity [Bq/kg] | f1 ≤ 1, f2 ≤ 240 | EN14411:2012 |
| Slip - BARE FOOT | | DIN EN 16165:2023-02, Attachment A |
| Slip - BARE FOOT α _{barefoot} [°] | | EN 16165:2021, Attachment A |
| Slip resistance - R | R10 | DIN EN 16165:2023-02, Attachment B |
| Slip resistance (PTV) - risk of dry/wet slippage - slider 55 | | BS 7976-2:2002+A1:2013 / UKSRG |
| Slip resistance (PTV) - risk of dry/wet slippage - slider 96 | | BS 7976-2:2002+A1:2013 / UKSRG |
| Displacement area class / displacement surface | NPD - no performance determined | DIN 51130 |
| Emissions of volatile organic compounds (VOCs) - class | A+ | ISO 16000 |
| Thermal conductivity coefficient [W/m*K] | NPD - no performance determined | PN-EN 12664 |
| Safety class of glass products | NA - not applicable | PN-EN 12600 |
| Class UPEC | NA - not applicable | CSTB-Cahier 3778_V6 |

2. Documents

Certificate of product compliance with the Polish Standard No. 10/N/22, Certificate authorising the product to bear the safety mark No. 9/B/22, Hygienic Certificate No. B.BK.60111.0359.2023.

Signed for and on behalf of the manufacturer by:

Kazimierz Ruczyński - Production Manager
Opoczno on 2024/09/18

