

1. Unique identification code of the product-type:

5902610522277

2. Intended use or uses:

The ceramic tiles for internal walls in buildings and industrial facilities.

3. Manufacturer:

Ceramika Paradyż Sp. z o.o., ul. Piotrkowska 61, 26-300 Opoczno, Polska

4. Authorized representative:

NA - not applicable

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

Assessment system: 4

6a. Harmonised standard:

EN14411:2012

Notified unit/s:

NA - not applicable

6b. European Assessment Document:

NA - not applicable

European Technical Assessment:

NA - not applicable

Technical Assessment Body:

NA - not applicable

Notified unit/s:

NA - not applicable

7. Declared performances:

Essential characteristics	Levels and/or classes	Reference document
Reaction to fire	A1	EN14411:2012
Release of dangerous substances - glazed tiles:	-	-
- Lead [mg/dm ²]	≤ 0.8	EN14411:2012
- Cadmium [mg/dm ²]	≤ 0.07	EN14411:2012
- Other	NPD - no performance determined	EN14411:2012
Bond strength / adhesion [N/mm ²]:	-	-
- cementitious adhesives	≥ 0.5	EN14411:2012
- dispersion adhesives	≥ 1	EN14411:2012
- reaction resin adhesives	≥ 2	EN14411:2012
- mortar	NPD - no performance determined	EN14411:2012
Thermal shock resistance	Pass	EN14411:2012
Breaking strength [N]		EN14411:2012
Slipperiness according to CEN/TS 16165:2021, Annex B - α_{shod} [°]	NA - not applicable	EN14411:2012
Tactility	NPD - no performance determined	EN14411:2012
Durability for:	-	-
- internal uses	Pass	EN14411:2012
- external uses: freeze-thaw resistance	NA - not applicable	EN14411:2012

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

NA - not applicable

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Karol Goździk - Production Manager

Tomaszów Mazowiecki on 2024/04/15



Applies to the product: NEVE CREATIVE NERO ŚCIANA DEKOR REKT. POLYSK 29,8X89,8 G1
Group: BIII

1. Detailed information about the application:

Tiles should be protected from low temperatures.

Characteristics	Levels and/or classes	Reference document
Thickness	9.0 mm	EN14411:2012
The permissible deviation of the average width for each tile from the work size width	± 0.5 %; ± 2.0 mm	EN14411:2012
The permissible deviation of the average length for each tile from the work size length	± 0.5 %; ± 2.0 mm	EN14411:2012
The permissible deviation of the average thickness of each tile from the work size thickness	± 10 %; ± 0.5 mm	EN14411:2012
The maximum permissible deviation from straightness, related to the corresponding work size (width)	± 0.3 %; ± 1.5 mm	EN14411:2012
The maximum permissible deviation from straightness, related to the corresponding work size (length)	± 0.5 %; ± 1.5 mm	EN14411:2012
The maximum permissible deviation from rectangularity related to the corresponding work size (width)	± 0.5 %; ± 2.0 mm	EN14411:2012
The maximum permissible deviation from rectangularity related to the corresponding work size (length)	± 0.5 %; ± 2.0 mm	EN14411:2012
The maximum permissible deviation from flatness centre curvature, related to diagonal calculated from the work sizes	+ 0.5 % / - 0.3 %; + 2.0 mm / - 1.5 mm	EN14411:2012
The maximum permissible deviation from flatness edge curvature, related to the corresponding work size (width)	+ 0.5 % / - 0.3 %; + 2.0 mm / - 1.5 mm	EN14411:2012
The maximum permissible deviation from flatness edge curvature, related to the corresponding work size (length)	+ 0.5 % / - 0.3 %; + 2.0 mm / - 1.5 mm	EN14411:2012
The maximum permissible deviation from flatness warpage, related to diagonal calculated from the work sizes	± 0.5 %; ± 2.0 mm	EN14411:2012
Water absorption E _b [%]	> 10	EN14411:2012
Breaking strength [N]		EN14411:2012
Flexural tensile strength [N/mm ²]		EN14411:2012
Resistance to deep abrasion - unglazed tiles [mm ³]	NA - not applicable	EN14411:2012
Resistance to surface abrasion - glazed tiles, PEI/number of rotations	NA - not applicable	EN14411:2012
Crazing resistance - glazed tiles	Pass	EN14411:2012
Impact resistance	NPD - no performance determined	EN14411:2012
Resistance to staining	minimum 4 class	EN14411:2012
Resistance to low concentrations of acids and alkalis	LA class	EN14411:2012
Resistance to high concentrations of acids and alkalis	NA - not applicable	EN14411:2012
Resistance to household chemicals and swimming pool salts	A class	EN14411:2012
Natural radioactivity [Bq/kg]	f1 ≤ 1, f2 ≤ 240	EN14411:2012
Slip - BARE FOOT	NA - not applicable	DIN EN 16165:2023-02, Attachment A
Slip - BARE FOOT α _{barefoot} [°]	NA - not applicable	EN 16165:2021, Attachment A
Slip resistance - R	NA - not applicable	DIN EN 16165:2023-02, Attachment B
Slip resistance (PTV) - risk of dry/wet slippage - slider 55	NA - not applicable	BS 7976-2:2002+A1:2013 / UKSRG
Slip resistance (PTV) - risk of dry/wet slippage - slider 96	N/A - not applicable	BS 7976-2:2002+A1:2013 / UKSRG
Displacement area class / displacement surface	NA - not applicable	DIN 51130
Emissions of volatile organic compounds (VOCs) - class	A+	ISO 16000
Thermal conductivity coefficient [W/m*K]	NPD - no performance determined	PN-EN 12664
Safety class of glass products	NA - not applicable	PN-EN 12600

2. Documents

Certificate of product compliance with the Polish Standard No. 52/N/22; Certificate authorising the product to bear the safety mark No. 51/B/22; Hygienic Certificate No. B-BK-60211-0341/21.

Signed for and on behalf of the manufacturer by:

Karol Goździk - Production Manager
Tomaszów Mazowiecki on 2024/04/15

