

Applies to the product: UNIWERSALNA LISTWA METALOWA GOLD PROFIL 1X89,8 G1
Group: NA - not applicable

1. Detailed information about the application:

Characteristics	Levels and/or classes	Reference document
Thickness	7.5 mm	NA - not applicable
The permissible deviation of the average width for each tile from the work size width	± 0.9 mm	NA - not applicable
The permissible deviation of the average length for each tile from the work size length	± 0.6 %; ± 2.0 mm	NA - not applicable
The permissible deviation of the average thickness of each tile from the work size thickness	± 0.5 mm	NA - not applicable
The maximum permissible deviation from straightness, related to the corresponding work size (width)	± 0.75 mm	NA - not applicable
The maximum permissible deviation from straightness, related to the corresponding work size (length)	± 0.5 %; ± 1.5 mm	NA - not applicable
The maximum permissible deviation from rectangularity related to the corresponding work size (width)	± 0.75 mm	NA - not applicable
The maximum permissible deviation from rectangularity related to the corresponding work size (length)	± 0.5 %; ± 2.0 mm	NA - not applicable
The maximum permissible deviation from flatness centre curvature, related to diagonal calculated from the work sizes	± 0.5 %; ± 2.0 mm	NA - not applicable
The maximum permissible deviation from flatness edge curvature, related to the corresponding work size (width)	± 0.75 mm	NA - not applicable
The maximum permissible deviation from flatness edge curvature, related to the corresponding work size (length)	± 0.5 %; ± 2.0 mm	NA - not applicable
The maximum permissible deviation from flatness warpage, related to diagonal calculated from the work sizes	± 0.5 %; ± 2.0 mm	NA - not applicable
Water absorption E _b [%]	≤ 0.5	NA - not applicable
Breaking strength [N]	NA - not applicable	NA - not applicable
Flexural tensile strength [N/mm ²]	NPD - no performance determined	NA - not applicable
Resistance to deep abrasion - unglazed tiles [mm ³]	NA - not applicable	NA - not applicable
Resistance to surface abrasion - glazed tiles, PEI/number of rotations	NA - not applicable	NA - not applicable
Crazing resistance - glazed tiles	Pass	NA - not applicable
Impact resistance	NPD - no performance determined	NA - not applicable
Resistance to staining	minimum 3 class	NA - not applicable
Resistance to low concentrations of acids and alkalis	LA class	NA - not applicable
Resistance to high concentrations of acids and alkalis	NA - not applicable	NA - not applicable
Resistance to household chemicals and swimming pool salts	A class	NA - not applicable
Natural radioactivity [Bq/kg]	f1 ≤ 1, f2 ≤ 240	NA - not applicable
Slip - BARE FOOT	NPD - no performance determined	DIN EN 16165:2023-02, Attachment A
Slip - BARE FOOT α _{barefoot} [°]	NPD - no performance determined	EN 16165:2021, Attachment A
Slip resistance - R	NA - not applicable	DIN EN 16165:2023-02, Attachment B
Slip resistance (PTV) - risk of dry/wet slippage - slider 55	NA - not applicable	BS 7976-2:2002+A1:2013 / UKSRG
Slip resistance (PTV) - risk of dry/wet slippage - slider 96	N/A - not applicable	BS 7976-2:2002+A1:2013 / UKSRG
Displacement area class / displacement surface		DIN 51130
Emissions of volatile organic compounds (VOCs) - class	A+	ISO 16000
Thermal conductivity coefficient [W/m*K]	NPD - no performance determined	PN-EN 12664
Safety class of glass products	NA - not applicable	PN-EN 12600
Class UPEC	NA - not applicable	CSTB-Cahier 3778_V6

In accordance with the indicated use and properties declared in the DOP, the Product Data Sheet and observing the principles included in the assembly instructions in accordance with

2. Documents

NA - not applicable

Signed for and on behalf of the manufacturer by:

Kazimierz Ruczyński - Production Manager
on 2025/03/08

